

WHAT IS CLAIMED IS:

1. A communication system for a helmet comprising:
 - a magnet-side socket mounted on the helmet;
 - a magnet-body-side socket for detachably connecting to the magnet-side socket;
 - a connecting cable extending from the magnet-body-side socket; and
 - a communication unit connected to the magnet-body-side socket for communicating voices in which a relatively large physiological sound is not transmitted.
2. The communication system according to claim 1, wherein the magnet-side-body socket further comprises a connecting surface, the connecting surface having plurality of electrodes.
3. The communication system according to claim 1, wherein the magnet-side socket further comprises a connecting surface, the connecting surface of the magnet-side-body socket having a plurality of electrodes connected to the plurality of electrodes on the magnet-side socket.
4. The communication system according to claim 3, wherein the connecting surface of the magnet-side socket further comprises a South pole iron strip and a North pole iron strip.
5. The communication system according to claim 1, the communication unit

0385360-110501

093530-10607

4
1
2
3
4
5

— **Systeme**

voices.

12. The communication system according to claim 10, wherein the acoustic communication signal falls below the first reference value such that no communication voices are heard.

13. The communication system according to claim 9, wherein the delay circuit provides a five second delay.

14. The communication system according to claim 8, further comprising a second detecting circuit for detecting sneezing or coughing, the second detecting circuit having a level detecting circuit and a delay circuit.

15. The communication system according to claim 14, wherein the level detecting circuit in the second detecting circuit provides a signal with a second reference value, the second reference value being set to a value close to a minimum value of a signal level generated by the physiological sound.

16. The communication system according to claim 15, wherein the detecting level circuit in the second detecting circuit provides an output signal for 0.7 seconds when the signal is higher than the second reference value.

17. The communication system according to claim 1, wherein the communication unit further comprises an OR circuit for switching an output signal from a VOX circuit and an output signal from a second detecting circuit.

09985890-110601

18. The communication system according to claim 1, wherein the communication unit further comprises an operating switch for varying a reference value, a delay time for a delay circuit and a gain of a speaker amplifier.

19. The communication system according to claim 1, wherein the communication unit is detachable fixed to a vehicle.

20. The communication system according to claim 1, wherein the communication unit is transportable.

09000000-140001